

**Uses:**

The corona discharge PRO series ozone generators are designed for use as high output shock treatment tools all models have adjustable output for use in offices and other occupied areas. Ideal for use in garbage compactors, industrial restoration, auto detailing, mold restoration, crime scene cleanup, etc. All Crystal Air ozone generators are manufactured with the highest quality components to create the best ozone generators on the market today.



The PRO 3600-1 & 9000-2 are designed as up gradable ozone generators. They come equipped with one(3600-1) and two(9000-2) generator plate/s that allows for 1000(3600-1), & 2000(9000-2) mg/hr. If the ozone generator is found to be not quite large enough simply add up to four(3600-1), or eight(9000-2) generator plates increasing output to 3600 or 9000 mg/hr respectively.

**Special features**

The PRO 3600, 5000, and 9000 series comes equipped with 4" ozone output and fresh air input spouts. These "spouts" will hook up to a drier vent hose or 4" thin wall sewer pipe. This feature allows the installer to route clean dry air into the ozone generator or route the ozone to where it is needed.

**Supply Gas & Generation method:**

Supply Gas: Ambient Air  
Generation method: High output corona discharge ozone generation

**Ozone output:**

PRO 3600-1 - 1000mg/hr (up gradable to 3600mg/hr max. by addition of 4 more plates.)  
PRO 5000 - 5000mg/hr max.  
PRO 9000-2 - 2000mg/hr (up gradable to 9000mg/hr max. by addition of 8 more plates.)

**Controls:**

Standard controls on all 3 machines, on/off power switch, fully continuously adjustable output control.

**Options:**

Optional controls available:  
-Variable output control plus T48, shock treatment timer with 9 different one shot time settings 2, 4, 6, 8, 12, 18, 24, 36, & 48hr.  
-Variable output control plus T7D, 7 day digital timer, includes 4 on and 4 off functions per day

**Weight & Dimensions:**

Dimensions for all 3 models: 21"LX 5"W X 6.25"H  
Weight, PRO 3600-1 9.5lb, PRO 5000 12lb, PRO 9000-2 12lb

**Electrical:**

PRO 3600-1 120 Volt, .5 Amp, 60 Watt, 50/60Hz, 240 Volt, .2 Amp, 50 Watt, 50/60Hz  
PRO 5000 120 Volt, 1.0 Amp, 100 Watt, 50 - 60Hz, 240 Volt, 1.0 Amp, 50 Watt, 50 - 60Hz  
PRO 9000-2 120 Volt, .1.4 Amp, 160 Watt, 50 - 60Hz, 240 Volt, .7 Amp, 160 Watt, 50/60HZ  
(please note that for use on 240VAC, customer will need to supply their own IEC computer style cord, the cord is the same one used on every desktop computer in the world)

**Cabinet:**

Stainless steel inner chassis with high strength PVC cabinet and ABS 4" hose connector.

**Corona plate life expectancy:**

18-36 months of constant use. ( dependant on cleaning schedule, humidity, and other environmental contaminants).

**Maintenance:**

Under normal 24 hr/day use these PRO ozone generators should be cleaned every four to eight weeks using dish soap, water and a tooth brush. Cleaning frequency is highly dependant on the humidity level of the air that the ozone generator receives.

**Warranty:**

The PRO series ozone generators are warranted against defects in materials and workmanship for a period of 6 years from date of purchase. The generator plates are warranted for 6 months.