

Uses:

The PRO 700 is a small low cost ozone generator designed for use in small rooms and offices up to 3000 sq/ft for freshening the air, or light shock treat up to about a 300 sq/ft area. This unit has a variable control for adjusting the output. The output starts at approx 20 mg/hr and goes up to 700 mg/hr.

All Crystal Air ozone generators are manufactured with the highest quality components to create the best ozone generators on the market today.



The PRO 3400-1 is designed as up gradable ozone generator. It comes equipped with one generator plate that produces 1000mg/hr. If the ozone generator is found to be not quite large enough simply add up to four generator plates increasing output to 3600mg/hr.

Supply Gas & Generation method:

Supply Gas: Ambient Air

Generation method: High output corona discharge ozone generation

Ozone output:

PRO 700 - 700mg/hr

PRO 3400-1 - 1000mg/hr (up gradable to 3600mg/hr max. by addition of 4 more plates.)

Controls:

Standard controls on both machines, on/off power switch, fully continuously adjustable output control.

Weight & Dimensions:

Dimensions for both models: 6.5" H X 5.75" W X 13"L

Weight, PRO 700 6.8lb, PRO 3400-1 7lb

Electrical:

PRO 700-1 120 Volt, .2 Amp, 25 Watt, 50 - 60Hz or 240 Volt, .1 Amp, 25 Watt, 50/60Hz

PRO 3400-1 120 Volt, .5 Amp, 60 Watt, 50 - 60Hz, 240 Volt, .2 Amp, 50 Watt, 50/60Hz

(please note that for use on 240VAC, customer will need to supply their own IEC computer style cord, the cord is the same one used on every desktop computer in the world)

Cabinet construction:

Stainless steel inner chassis with high strength PVC cabinet.

Corona plate life expectancy:

18-36 months of constant use. (dependant on cleaning schedule, humidity, and other environmental contaminants).

Maintenance:

Under normal 24 hr/day use these PRO ozone generators should be cleaned every four to eight weeks using dish soap, water and a tooth brush. Cleaning frequency is highly dependant on the humidity level of the air that the ozone generator receives.

Warranty:

The PRO series ozone generators are warranted against defects in materials and workmanship for a period of 6 years from date of purchase. The generator plates are warranted for 6 months.